



Bearing No. 32215JR

D	130 mm
d	75 mm
T	33,25 mm
B	31 mm
C	27 mm
a	30,2 mm
e	0.44
Cr	218
Cu	36.4
Y0	0.76
Y1	1.38
C0r	234
Bore	2.953 Inch 75 Millimeter
Noun	Bearing
a(mm)	30.2
Da min	114 mm
da max	85 mm
Weight	1,77 Kg
r min.	2 mm
r(min)	2
UNSPSC	31171516
Db(min)	125
db(max)	85
Da(max)	121.5
Da(min)	114
r1(min)	1.5
Sa(min)	4
Sb(min)	6
ra(max)	2

rb(max)	1.5
da(min)	85
ra max.	2 mm
Db min.	125 mm
Da max.	121,5 mm
da min.	85 mm
r2 min.	1,5 mm
rb max.	1,5 mm
Oil lub.	3900
Category	Tapered Roller Bearings Assembly
Size (mm)	75x130x33.25
Component	Assembly
Inventory	0.0
Width (mm)	33,25
Grease lub.	2900
Bearing No.	32215JR
Basic Number	32215
Weight / LBS	3.902
Inch - Metric	Metric
Product Group	B04334
Other Features	High Load Capacity
Keyword String	Tapered
Assembly Width	1.309 Inch 33.25 Millimeter
Bearing number	32215JR
Precision Class	Standard
(Refer.)Mass(kg)	1.77
Manufacturer URL	http://www.koyousa.com
Long Description	Assembly; Standard Precision; 75MM Bore; 130MM Outside Diameter; 33.25MM Assembly Width; Single

	Row of Rollers
Outside Diameter	5.118 Inch 130 Millimeter
Weight / Kilogram	1.868
Manufacturer Name	KOYO
Bore Diameter (mm)	75
Outer Diameter (mm)	130
Minimum Buy Quantity	N/A
Number of Tapered Rows	Single Row
Harmonized Tariff Code	8482.20.00.00
Calculation factor (e)	0,44
Flange Outside Diameter	0 Inch 0 Millimeter
(Oil) Lubrication Speed	3900 r/min
Calculation factor (Y0)	0,76
Manufacturer Item Number	32215JR
(Grease) Lubrication Speed	2900 r/min
Basic static load rating (C0)	234 kN
Basic dynamic load rating (C)	174 kN