



Bearing No. 609

D	24 mm
d	9 mm
B	7 mm
C	7 mm
Cr	4.15
f0	12.8
Cu	0.060
C0r	1.40
Bore	0.354 Inch 9 Millimeter
Noun	Bearing
r(min)	0.3
Weight	0,015 Kg
UNSPSC	31171504
r min.	0,3 mm
r1 min.	0,3 mm
da min.	11 mm
ra max.	0,3 mm
da(min)	11
Da(max)	22
ra(max)	0.3
Da max.	22 mm
Oil lub.	40000
Category	Single Row Ball Bearing
Size (mm)	9x24x7
Snap Ring	No
Enclosure	Open
Inventory	0.0
Width (mm)	7
Bearing No.	609
Grease lub.	33000

Weight / LBS	0.0331
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric
Keyword String	Ball
Bearing number	609
Other Features	Deep Groove
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
(Refer.)Mass(g)	15
Manufacturer URL	http://www.koyousa.com
Inner Race Width	0 Inch 0 Millimeter
Long Description	9MM Bore; 24MM Outside Diameter; 7MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Outside Diameter	0.945 Inch 24 Millimeter
Outer Race Width	0.276 Inch 7 Millimeter
Manufacturer Name	KOYO
Weight / Kilogram	0
Internal Clearance	C0-Medium
Bore Diameter (mm)	9
Outer Diameter (mm)	24
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	40000 r/min
Internal Special Features	No
(Grease) Lubrication	33000 r/min

Speed	
Basic static load rating (C0)	1,4 kN
Basic dynamic load rating (C)	3,35 kN
Maximum Capacity / Filling Slot	No