



Bearing No. 609

C	7 mm
r	0.3
d	9 mm
D	24 mm
B	7 mm
D_	24
ra	0.3
fo	12.968
da	11
B0	7
Cr	340
B_	7
C0	1.43
Z_	7
D_a	22
DA_	3.969
DE_	20.469
SRE	2.22
C0r	146
SRI	2.04
DI_	12.531
Noun	Bearing
SRIX	0.015
mass	14.5
SREX	0.03
SRIN	-0.015
Bore	0.354 Inch 9 Millimeter
SREN	0
SDM_	16.5
KBRG	6101

yobi	609
r min.	0,3 mm
LangID	1
UNSPSC	31171504
Weight	0,0145 Kg
GRS rpm	32000
da min.	11 mm
hidYobi	609
Da max.	22,8 mm
ra max.	0,3 mm
Oil rpm	38000
Category	Single Row Ball Bearing
hidTable	ecat_NSESBM
Size (mm)	9x24x7
Inventory	0.0
Enclosure	Open
Snap Ring	No
Width (mm)	7
Prod_Type3	ESM_MD_OT
Weight / LBS	0.03234
Cage Material	Steel
Product Group	B00308
Inch - Metric	Metric
Bearing number	609
Keyword String	Ball
Other Features	Deep Groove
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outer Race Width	0.276 Inch 7 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Long Description	9MM Bore; 24MM Outside Diameter; 7MM Outer Race Width;

	Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Manufacturer URL	http://www.nskamericas.com
Outside Diameter	0.945 Inch 24 Millimeter
Weight / Kilogram	0.014
Manufacturer Name	NSK
Internal Clearance	C0-Medium
Bore Diameter (mm)	9
Outer Diameter (mm)	24
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Internal Special Features	No
(Grease) Lubrication Speed	32 000 r/min
Basic static load rating (C0)	1,43 kN
Basic dynamic load rating (C)	3,35 kN
Maximum Capacity / Filling Slot	No