



Bearing No. EE134100/134143

|                                 |                    |
|---------------------------------|--------------------|
| R                               | 6,3 mm             |
| a                               | 5,1 mm             |
| d                               | 254 mm             |
| D                               | 365,125 mm         |
| T                               | 58,738 mm          |
| B                               | 58,738 mm          |
| C                               | 42,862 mm          |
| r                               | 6,3 mm             |
| Ab                              | 1,7 mm             |
| Aa                              | 8,3 mm             |
| Db                              | 339 mm             |
| da                              | 272 mm             |
| db                              | 281 mm             |
| Da                              | 347 mm             |
| Weight                          | 18,03 Kg           |
| Size (mm)                       | 254x365.125x58.738 |
| Width (mm)                      | 58,738             |
| Factor (K)                      | 1,56               |
| Factor (G1)                     | 1327,7             |
| Factor (Cg)                     | 0,0433             |
| Factor (G2)                     | 187,2              |
| Bearing number                  | EE134100/134143    |
| Bore Diameter (mm)              | 254                |
| Outer Diameter (mm)             | 365,125            |
| Calculation factor (e)          | 0,37               |
| Basic static load rating (C0)   | 1330 kN            |
| Basic dynamic load rating (C1)  | 666 kN             |
| Basic dynamic load rating (C90) | 173                |



|                                  |     |
|----------------------------------|-----|
| Basic dynamic load rating (Ca90) | 111 |
|----------------------------------|-----|