



Bearing No. EE 526130/526190

a	90 mm
d	330.2 mm
D	482.6 mm
T	85.725 mm
B	80.167 mm
C	60.325 mm
Size (mm)	482.6x330.2x85.725
Width (mm)	85,725
Mass bearing	48.5 kg
d ₁	402 mm
Limiting speed	1300 r/min
Bearing number	EE 526130/526190
Reference speed	850 r/min
Dimension series	EE 526000
D _b min.	454 mm
D _a min.	431 mm
d _b min.	362 mm
d _a max.	366 mm
C _a min.	6 mm
C _b min.	25 mm
r _a max.	6 mm
r _b max.	3.1 mm
Bore Diameter (mm)	482,6
D _a max.	465 mm
Outer Diameter (mm)	330,2
Calculation factor e	0.4
Calculation factor Y	1.5
r _b - max.	3.1 mm
r _a - max.	6 mm
C _b - min.	25 mm

C_a - min.	11 mm
D_b - min.	454 mm
D_a - max.	465 mm
$r_{1,2}$ min.	6.4 mm
$r_{3,4}$ min.	3.3 mm
D_a - min.	431 mm
d_b - min.	362 mm
d_a - max.	366 mm
d_1 ?	402 mm
$r_{3,4}$ - min.	3.3 mm
$r_{1,2}$ - min.	6.4 mm
Calculation factor - Y	1.5
Calculation factor - e	0.4
Basic dynamic load rating C	1210 kN
Basic dynamic load rating - C	1210 kN
Fatigue load limit P_u	204 kN
Calculation factor Y_0	0.8
Calculation factor - Y_0	0.8
Fatigue load limit - P_u	212 kN
Basic static load rating C_0	2500 kN
Basic static load rating - C_0	2500 kN