



Bearing No. EE 763330/763410

a	177 mm
d	838.2 mm
D	1041.4 mm
T	93.662 mm
B	88.9 mm
C	66.675 mm
Size (mm)	1041.4x838.2x93.662
Width (mm)	93,662
Mass bearing	160 kg
d ₁	925.8 mm
Limiting speed	460 r/min
Bearing number	EE 763330/763410
Reference speed	320 r/min
Dimension series	EE 763000
D _b min.	1001 mm
D _a min.	975 mm
d _b min.	870 mm
d _a max.	894 mm
C _a min.	3 mm
C _b min.	26.5 mm
r _a max.	6 mm
r _b max.	6 mm
Bore Diameter (mm)	1041,4
D _a max.	1010 mm
Outer Diameter (mm)	838,2
Calculation factor e	0.44
Calculation factor Y	1.35
r _b - max.	6 mm
r _a - max.	6 mm
C _b - min.	26.5 mm

C_a - min.	10 mm
D_b - min.	1001 mm
D_a - max.	1010 mm
$r_{1,2}$ min.	6.4 mm
$r_{3,4}$ min.	6.4 mm
D_a - min.	975 mm
d_b - min.	870 mm
d_a - max.	894 mm
d_1 ?	925.8 mm
$r_{3,4}$ - min.	6.4 mm
$r_{1,2}$ - min.	6.4 mm
Calculation factor - Y	1.35
Calculation factor - e	0.44
Basic dynamic load rating C	2010 kN
Basic dynamic load rating - C	1900 kN
Fatigue load limit P_u	345 kN
Calculation factor Y_0	0.8
Calculation factor - Y_0	0.8
Fatigue load limit - P_u	320 kN
Basic static load rating C_0	5200 kN
Basic static load rating - C_0	4800 kN