



Bearing No. 32252

C	106 mm
e	0.43
d	260 mm
D	480 mm
T	137 mm
B	130 mm
a	115,2 mm
Y0	0.77
Y1	1.39
Cu	276
Cr	2200
C0r	2870
a(mm)	115.2
r min.	6 mm
da max	300 mm
Da min	400 mm
r(min)	6
Weight	102 Kg
r1(min)	5
db(max)	300
da(min)	288
Sb(min)	30
Da(max)	458
Sa(min)	16
Da(min)	400
ra(max)	5
rb(max)	4
Db(min)	455
rb max.	4 mm
ra max.	5 mm

Db min.	455 mm
Da max.	458 mm
da min.	288 mm
r2 min.	5 mm
Oil lub.	880
Size (mm)	260x480x137
Width (mm)	137
Bearing No.	32252
Grease lub.	660
Bearing number	32252
(Refer.)Mass(kg)	102
Bore Diameter (mm)	260
Outer Diameter (mm)	480
Calculation factor (e)	0,43
Calculation factor (Y0)	0,77
(Oil) Lubrication Speed	880 r/min
(Grease) Lubrication Speed	660 r/min
Basic static load rating (C0)	2870 kN
Basic dynamic load rating (C)	1760 kN