



Bearing No. 32252

D	480 mm
d	260 mm
T	137 mm
B	130 mm
C	106 mm
a	116 mm
e	0.45
Cr	194000
Y0	0.73
db	305
da	302
Y1	1.3
B_	130
Sb	31
C0	3300
Sa	14
D_	480
Z_	20
C_	106
C0r	335000
DA_	48.329
Iso	-
DE_	413.735
D_b	446
DI_	320.69
SBRG	22
SDM_	367.213
D_a2	394
KBRG	3111
yobi	32252

D_a1	458
mass	103
TC-RA	770.828
r min.	6 mm
Weight	103 Kg
TC-DA1	51.558
TC-DA2	45.099
TC-SLR	97
Da min	394 mm
LangID	1
ALPHA_	16.667
Db min.	446 mm
Oil rpm	950
db max.	305 mm
Da max.	458 mm
ra max.	5 mm
hidYobi	32252
da min.	293 mm
T-ALP21	33
rb max.	4 mm
T-ALP22	20
T-ALP23	0
GRS rpm	670
inner r	6
outer r	5
r1 min.	5 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	3
inner ra	5
outer rb	4
TC-BET22	50

Size (mm)	260x480x137
Width (mm)	137
Prod_Type3	TRBSR_MD_A
Bearing number	32252
Bore Diameter (mm)	260
Outer Diameter (mm)	480
Calculation factor (e)	0,45
Calculation factor (Y0)	0,73
(Oil) Lubrication Speed	950 r/min
(Grease) Lubrication Speed	670 r/min
Basic dynamic load rating (C)	1900 kN
Basic static load rating (C0)	3300 kN