



Bearing No. 7028 ACD/HCP4A

D	210 mm
d	140 mm
B	33 mm
a	57.5 mm
Ball - z	22
Size (mm)	210x140x33
Width (mm)	33
Mass bearing	2.83 kg
d _n	166.3 mm
d _n	166.3 mm
D ₁	188.4 mm
d ₁	161.6 mm
d ₂	161.6 mm
D ₁	188.4 mm
d ₂	161.6 mm
d ₁	161.6 mm
Bearing number	7028 ACD/HCP4A
Preload class B	530 N/micron
Preload class A	404 N/micron
Preload class D	950 N/micron
Preload class C	702 N/micron
G _{ref}	45 cm3
Number of balls z	22
Bore Diameter (mm)	210
r _b max.	1 mm
r _a max.	2 mm
D _b max.	205 mm
D _a max.	201 mm
d _a min.	149 mm

d_b min.	149 mm
Outer Diameter (mm)	140
D_b - max.	205 mm
d_b - min.	149 mm
Ball - D_w	22.225 mm
$r_{1,2}$ min.	2 mm
$r_{3,4}$ min.	1 mm
d_a - min.	149 mm
r_a - max.	2 mm
D_a - max.	201 mm
r_b - max.	1 mm
Calculation factor f	1.16
Calculation factor e	0.68
$r_{1,2}$ - min.	2 mm
$r_{3,4}$ - min.	1 mm
Calculation factor - e	0.68
Calculation factor - f	1.16
Ball diameter D_w	22.225 mm
Basic dynamic load rating C	146 kN
Preload class C G_C	3600 N
Preload class B G_B	1800 N
Preload class A G_A	900 N
Preload class D G_D	7200 N
Basic dynamic load rating - C	146 kN
Preload class B - G_B	1800 N
Preload class D - G_D	7200 N
Preload class C - G_C	3600 N
Preload class A - G_A	900 N
Fatigue load limit P_u	5.1 kN
Calculation factor f_1	0.99

Calculation factor f_{2A}	1
Calculation factor f_{2C}	1.05
Calculation factor f_{2B}	1.02
Calculation factor f_{2D}	1.08
Calculation factor f_{HC}	1.02
Calculation factor - X_2	0.67
Calculation factor - f_1	0.99
Calculation factor - Y_1	0.92
Limiting speed for oil lubrication	11000 mm/min
Calculation factor - Y_0	0.76
Fatigue load limit - P_u	5.1 kN
Calculation factor - Y_2	1.41
Calculation factor - f_{HC}	1.02
Calculation factor - f_{2A}	1
Calculation factor - f_{2C}	1.05
Calculation factor - f_{2B}	1.02
Calculation factor - f_{2D}	1.08
Limiting speed for grease lubrication	7000 r/min
Basic static load rating C_0	156 kN
Static axial stiffness, preload class B	530 N/μm
Attainable speed for grease lubrication	7000 r/min
Static axial stiffness, preload class D	950 N/μm
Static axial stiffness, preload class C	702 N/μm
Static axial stiffness, preload class A	404 N/μm
Basic static load rating -	156 kN

C_0	
Attainable speed for oil-air lubrication	11000 r/min
Reference grease quantity G_{ref}	45 cm ³
Calculation factor (single, tandem) Y_2	0.87
Calculation factor (single, tandem) Y_0	0.38
Calculation factor (single, tandem) X_2	0.41
Calculation factor (back-to-back, face-to-face) Y_1	0.92
Calculation factor (back-to-back, face-to-face) Y_2	1.41
Calculation factor (back-to-back, face-to-face) Y_0	0.76
Calculation factor (back-to-back, face-to-face) X_2	0.67