



Bearing No. 32308JR

D	90 mm
d	40 mm
T	35,25 mm
B	33 mm
C	27 mm
a	24,3 mm
e	0.35
Cr	145
Y0	0.96
Y1	1.74
Cu	21.3
C0r	139
Bore	1.575 Inch 40 Millimeter
Noun	Bearing
a(mm)	24.3
Da min	73 mm
da max	50 mm
Weight	1,06 Kg
r min.	2 mm
r(min)	2
UNSPSC	31171516
Db(min)	82
db(max)	50
Da(max)	80
Da(min)	73
r1(min)	1.5
Sa(min)	3
Sb(min)	8
ra(max)	2

rb(max)	1.5
da(min)	50
ra max.	2 mm
Db min.	82 mm
Da max.	80 mm
da min.	50 mm
r2 min.	1,5 mm
rb max.	1,5 mm
Oil lub.	6200
Category	Tapered Roller Bearings Assembly
Size (mm)	40x90x35.25
Component	Assembly
Inventory	0.0
Width (mm)	35,25
Grease lub.	4600
Bearing No.	32308JR
Basic Number	32308
Weight / LBS	2.337
Inch - Metric	Metric
Product Group	B04334
Other Features	High Load Capacity
Keyword String	Tapered
Assembly Width	1.388 Inch 35.25 Millimeter
Bearing number	32308JR
Precision Class	Standard
(Refer.)Mass(kg)	1.06
Outside Diameter	3.543 Inch 90 Millimeter
Manufacturer URL	http://www.koyousa.com
Long Description	Assembly; Standard Precision; 40MM Bore; 90MM Outside

	Diameter; 35.25MM Assembly Width; Single Row of Rollers
Weight / Kilogram	1.06
Manufacturer Name	KOYO
Bore Diameter (mm)	40
Outer Diameter (mm)	90
Minimum Buy Quantity	N/A
Calculation factor (e)	0,35
Number of Tapered Rows	Single Row
Harmonized Tariff Code	8482.20.00.00
Flange Outside Diameter	0 Inch 0 Millimeter
(Oil) Lubrication Speed	6200 r/min
Calculation factor (Y0)	0,96
Manufacturer Item Number	32308JR
(Grease) Lubrication Speed	4600 r/min
Basic static load rating (C0)	139 kN
Basic dynamic load rating (C)	116 kN