



Bearing No. NU2328

E	260 mm
d	140 mm
D	300 mm
B	102 mm
C	102 mm
F	180 mm
D1	245 mm
Fw	180 mm
Da max	284 mm
db min	182 mm
da max	176 mm
da min	156 mm
rs min	4 mm
ra max	3 mm
r min.	4 mm
Weight	33,8 Kg
r1 min.	4 mm
Size (mm)	140x300x102
Nlim (oil)	2,300 rpm
Width (mm)	102
Nlim (grease)	2,000 rpm
Bearing number	NU2328
Dynamic load, C	920 kN
Static load, C0	1,250 kN
Bore Diameter (mm)	140
Outer Diameter (mm)	300
Mass (without HJ ring)	33.8 kg
Radial clearance class	CN
(Grease) Lubrication Speed	2 000 r/min

Basic dynamic load rating (C)	920 kN
Basic static load rating (C0)	1 250 kN
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.41 Hz
Characteristic outer ring frequency, BPF0	5.73 Hz
Characteristic inner ring frequency, BRFI	8.27 Hz
Characteristic rolling element frequency, BSF	5.32 Hz