




Bearing No. 7034 ACD/P4AL

b	2.8 mm
d	170 mm
a	71.4 mm
B	42 mm
D	260 mm
Ball - z	22
Size (mm)	260x170x42
Width (mm)	42
Mass bearing	6.99 kg
d ₂	198.7 mm
D ₁	231.3 mm
d _n	205.8 mm
C ₁	23.8 mm
C ₂	7.1 mm
C ₃	7.1 mm
C ₂	7.1 mm
C ₁	23.8 mm
d _n	205.8 mm
D ₁	231.3 mm
d ₂	198.7 mm
d ₁	198.7 mm
d ₁	198.7 mm
C ₃	7.1 mm
Bearing number	7034 ACD/P4AL
Preload class B	563 N/micron
Preload class A	433 N/micron
G _{ref}	84 cm3
Preload class D	1003 N/micron
Preload class C	744 N/micron

Number of balls z	22
Bore Diameter (mm)	260
r_b max.	1 mm
r_a max.	2 mm
D_b max.	254 mm
D_a max.	249 mm
d_a min.	181 mm
d_b min.	181 mm
Outer Diameter (mm)	170
r_b - max.	1 mm
d_b - min.	181 mm
d_a - min.	181 mm
D_b - max.	254 mm
$r_{1,2}$ min.	2.1 mm
$r_{3,4}$ min.	1.1 mm
D_a - max.	249 mm
r_a - max.	2 mm
Ball - D_w	26.988 mm
Calculation factor f	1.14
Calculation factor e	0.68
Calculation factor - f	1.14
$r_{1,2}$ - min.	2.1 mm
$r_{3,4}$ - min.	1.1 mm
Calculation factor - e	0.68
Ball diameter D_w	26.988 mm
Basic dynamic load rating C	199 kN
Preload class A G_A	1250 N
Preload class B G_B	2500 N
Preload class C G_C	5000 N
Basic dynamic load rating - C	199 kN
Preload class D G_D	10000 N

Preload class C - G_C	5000 N
Preload class B - G_B	2500 N
Preload class A - G_A	1250 N
Preload class D - G_D	10000 N
Fatigue load limit P_u	6.7 kN
Calculation factor f_1	0.99
Calculation factor f_{2A}	1
Calculation factor f_{2B}	1.02
Calculation factor f_{2C}	1.05
Calculation factor f_{2D}	1.08
Calculation factor f_{HC}	1
Calculation factor - Y_0	0.76
Calculation factor - Y_2	1.41
Calculation factor - Y_1	0.92
Calculation factor - f_1	0.99
Calculation factor - X_2	0.67
Fatigue load limit - P_u	6.7 kN
Limiting speed for oil lubrication	7000 mm/min
Calculation factor - f_{2B}	1.02
Calculation factor - f_{HC}	1
Calculation factor - f_{2D}	1.08
Calculation factor - f_{2C}	1.05
Calculation factor - f_{2A}	1
Limiting speed for grease lubrication	4800 r/min
Basic static load rating C_0	232 kN
Static axial stiffness, preload class A	433 N/ μ m
Static axial stiffness,	1003 N/ μ m

preload class D	
Static axial stiffness, preload class C	744 N/ μ m
Static axial stiffness, preload class B	563 N/ μ m
Attainable speed for grease lubrication	4800 r/min
Attainable speed for oil- air lubrication	7000 r/min
Basic static load rating - C_0	232 kN
Reference grease quantity G_{ref}	84 cm ³
Calculation factor (single, tandem) Y_2	0.87
Calculation factor (single, tandem) Y_0	0.38
Calculation factor (single, tandem) X_2	0.41
Calculation factor (back- to-back, face-to-face) Y_1	0.92
Calculation factor (back- to-back, face-to-face) Y_2	1.41
Calculation factor (back- to-back, face-to-face) Y_0	0.76
Calculation factor (back- to-back, face-to-face) X_2	0.67