



Bearing No. 32315JR

D	160 mm
d	75 mm
T	58 mm
B	55 mm
C	45 mm
a	40 mm
e	0.35
Cr	454
Cu	64.6
Y0	0.96
Y1	1.74
C0r	481
Bore	2.953 Inch 75 Millimeter
Noun	Bearing
a(mm)	40.0
Da min	133 mm
da max	91 mm
Weight	5,41 Kg
r min.	3 mm
r(min)	3
UNSPSC	31171516
Db(min)	149
db(max)	91
Da(max)	148
Da(min)	133
r1(min)	2.5
Sa(min)	4
Sb(min)	13
ra(max)	2.5

rb(max)	2
da(min)	89
ra max.	2,5 mm
Db min.	149 mm
Da max.	148 mm
da min.	89 mm
r2 min.	2,5 mm
rb max.	2 mm
Oil lub.	3300
Category	Tapered Roller Bearings Assembly
Size (mm)	75x160x58
Component	Assembly
Inventory	0.0
Width (mm)	58
Grease lub.	2500
Bearing No.	32315JR
Basic Number	32315
Weight / LBS	11.927
Inch - Metric	Metric
Product Group	B04334
Other Features	High Load Capacity
Keyword String	Tapered
Assembly Width	2.283 Inch 58 Millimeter
Bearing number	32315JR
Precision Class	Standard
(Refer.)Mass(kg)	5.41
Outside Diameter	6.299 Inch 160 Millimeter
Manufacturer URL	http://www.koyousa.com
Long Description	Assembly; Standard Precision; 75MM Bore; 160MM Outside

	Diameter; 58MM Assembly Width; Single Row of Rollers
Weight / Kilogram	5.42
Manufacturer Name	KOYO
Bore Diameter (mm)	75
Outer Diameter (mm)	160
Minimum Buy Quantity	N/A
Calculation factor (e)	0,35
Number of Tapered Rows	Single Row
Harmonized Tariff Code	8482.20.00.00
Flange Outside Diameter	0 Inch 0 Millimeter
(Oil) Lubrication Speed	3300 r/min
Calculation factor (Y0)	0,96
Manufacturer Item Number	32315JR
(Grease) Lubrication Speed	2500 r/min
Basic static load rating (C0)	481 kN
Basic dynamic load rating (C)	363 kN