



Bearing No. 32317JR

D	180 mm
d	85 mm
T	63,5 mm
B	60 mm
C	49 mm
a	43,8 mm
e	0.35
Cr	549
Cu	77.6
Y0	0.96
Y1	1.74
C0r	587
Bore	3.346 Inch 85 Millimeter
Noun	Bearing
a(mm)	43.8
Da min	150 mm
da max	103 mm
Weight	7,42 Kg
r min.	4 mm
r(min)	4
UNSPSC	31171516
Db(min)	167
db(max)	103
Da(max)	166
Da(min)	150
r1(min)	3
Sa(min)	5
Sb(min)	14.5
ra(max)	3

rb(max)	2.5
da(min)	103
ra max.	3 mm
Db min.	167 mm
Da max.	166 mm
da min.	103 mm
r2 min.	3 mm
rb max.	2,5 mm
Oil lub.	3000
Category	Tapered Roller Bearings Assembly
Size (mm)	85x180x63.5
Component	Assembly
Inventory	0.0
Width (mm)	63,5
Grease lub.	2200
Bearing No.	32317JR
Basic Number	32317
Weight / LBS	16.358
Inch - Metric	Metric
Product Group	B04334
Other Features	High Load Capacity
Keyword String	Tapered
Assembly Width	2.5 Inch 63.5 Millimeter
Bearing number	32317JR
Precision Class	Standard
(Refer.)Mass(kg)	7.42
Manufacturer URL	http://www.koyousa.com
Long Description	Assembly; Standard Precision; 85MM Bore; 180MM Outside Diameter; 63.5MM Assembly Width; Single Row of Rollers

Outside Diameter	7.087 Inch 180 Millimeter
Weight / Kilogram	7.43
Manufacturer Name	KOYO
Bore Diameter (mm)	85
Outer Diameter (mm)	180
Minimum Buy Quantity	N/A
Number of Tapered Rows	Single Row
Harmonized Tariff Code	8482.20.00.00
Calculation factor (e)	0,35
Flange Outside Diameter	0 Inch 0 Millimeter
(Oil) Lubrication Speed	3000 r/min
Calculation factor (Y0)	0,96
Manufacturer Item Number	32317JR
(Grease) Lubrication Speed	2200 r/min
Basic static load rating (C0)	587 kN
Basic dynamic load rating (C)	439 kN