



Bearing No. 32321-A

| | |
|---------------------|--|
| D | 225 mm |
| d | 105 mm |
| T | 81,5 mm |
| a | 56 mm |
| B | 77 mm |
| C | 63 mm |
| Y | 1,74 |
| e | 0,35 |
| m | 15,9 kg / Weight |
| Size (mm) | 105x225x81.5 |
| Width (mm) | 81,5 |
| n_B | 2220 1/min / Reference speed |
| n_G | 3100 1/min / Limiting speed |
| Y_0 | 0,96 |
| C_r | 670000 N |
| d_1 | 160,9 mm |
| C_{0r} | 930000 N / Static load rating (radial) |
| C_{ur} | 103000 N / Fatigue limit load, radial |
| Bearing number | 32321-A |
| $D_{b \text{ min}}$ | 209 mm |
| $d_{a \text{ max}}$ | 128 mm |
| $d_{b \text{ min}}$ | 119 mm |
| $r_{a \text{ max}}$ | 4 mm |
| $r_{b \text{ max}}$ | 3 mm |
| $D_{a \text{ min}}$ | 185 mm |
| $D_{a \text{ max}}$ | 211 mm |

| | |
|------------------------|---------|
| $C_{b \text{ min}}$ | 18,5 mm |
| $C_{a \text{ min}}$ | 9 mm |
| Bore Diameter (mm) | 105 |
| Outer Diameter (mm) | 225 |
| $r_{1, 2 \text{ min}}$ | 4 mm |
| $r_{3, 4 \text{ min}}$ | 3 mm |