



Bearing No. 32332

|         |         |
|---------|---------|
| C       | 95 mm   |
| e       | 0.35    |
| d       | 160 mm  |
| D       | 340 mm  |
| T       | 121 mm  |
| B       | 114 mm  |
| a       | 83 mm   |
| Y0      | 0.95    |
| Y1      | 1.73    |
| Cu      | 187     |
| Cr      | 1530    |
| C0r     | 1720    |
| a(mm)   | 83.0    |
| r min.  | 5 mm    |
| da max  | 200 mm  |
| Da min  | 277 mm  |
| r(min)  | 5       |
| Weight  | 47,9 Kg |
| r1(min) | 4       |
| db(max) | 200     |
| da(min) | 182     |
| Sb(min) | 18      |
| Da(max) | 322     |
| Sa(min) | 10      |
| Da(min) | 277     |
| ra(max) | 4       |
| rb(max) | 3       |
| Db(min) | 316     |
| rb max. | 3 mm    |
| ra max. | 4 mm    |
|         |         |

|                               |             |
|-------------------------------|-------------|
| Db min.                       | 316 mm      |
| Da max.                       | 322 mm      |
| da min.                       | 182 mm      |
| r2 min.                       | 4 mm        |
| Oil lub.                      | 1400        |
| Size (mm)                     | 160x340x121 |
| Width (mm)                    | 121         |
| Bearing No.                   | 32332       |
| Grease lub.                   | 1100        |
| Bearing number                | 32332       |
| (Refer.)Mass(kg)              | 47.9        |
| Bore Diameter (mm)            | 160         |
| Outer Diameter (mm)           | 340         |
| Calculation factor (e)        | 0,35        |
| Calculation factor (Y0)       | 0,95        |
| (Oil) Lubrication Speed       | 1400 r/min  |
| (Grease) Lubrication Speed    | 1100 r/min  |
| Basic static load rating (C0) | 1720 kN     |
| Basic dynamic load rating (C) | 1220 kN     |