



**Bearing No. 32352**

e	0.37
d	260 mm
D	540 mm
T	176 mm
B	165 mm
C	136 mm
a	130,5 mm
db	328
B_	165
Y0	0.88
da	309
C0	4800
Sa	13
Sb	40
Z_	18
Y1	1.6
C_	136
Cr	297000
D_	540
Iso	-
D_b	495
C0r	490000
SDM_	400.875
mass	188
SBRG	23
D_a2	441
KBRG	3114
yobi	32352
D_a1	512
TC-RA	0

LangID	1
TC-SLR	0
Da min	441 mm
ALPHA_	14
r min.	6 mm
TC-DA1	0
TC-DA2	0
Weight	188 Kg
hidYobi	32352
Oil rpm	850
T-ALP21	0
GRS rpm	630
ra max.	5 mm
Db min.	495 mm
rb max.	5 mm
db max.	328 mm
T-ALP22	0
Da max.	512 mm
da min.	293 mm
r1 min.	6 mm
inner r	6
outer r	6
T-ALP23	0
TC-BET22	0
TC-BET21	0
hidTable	ecat_NSTPRM
TC-BET23	0
inner ra	5
outer rb	5
Size (mm)	260x540x176
Width (mm)	176
Prod_Type3	TRBSR_MD_A

Bearing number	32352
Bore Diameter (mm)	260
Outer Diameter (mm)	540
Calculation factor (e)	0,37
(Oil) Lubrication Speed	850 r/min
Calculation factor (Y0)	0,88
(Grease) Lubrication Speed	630 r/min
Basic dynamic load rating (C)	2910 kN
Basic static load rating (C0)	4800 kN