



Bearing No. K18X22X17H

Fw	18 mm
Ew	22 mm
Bc	17 mm
Cr	13.3
Cu	3.10
P/S	S
C0r	19.9
Noun	Bearing
Bore	0.709 Inch 18 Millimeter
Width	0.669 Inch 17 Millimeter
UNSPSC	31171512
Weight	0.009 Kg
Retainer	Yes
Oil lub.	24000
Category	Needle Non Thrust Roller Bearing
Inventory	0.0
Separable	No
Component	Roller Assembly Only
Enclosure	Not Applicable
Closed End	Not Applicable
Grease lub.	16000
Bearing No.	K18X22X17H
Shaft(max.)	18.000
Shaft(min.)	17.992
Weight / LBS	0.02
Housing(max.)	22.020
Housing(min.)	22.007
Inch - Metric	Metric

Product Group	B04144
Self Aligning	No
Other Features	Radial Roller Hardened Steel Cage
Bearing number	K18X22X17H
Keyword String	Needle
Thrust Bearing	No
Rolling Element	Needle Roller Bearing
Outside Diameter	0.866 Inch 22 Millimeter
Long Description	18MM Bore; 22MM Outside Diameter; 17MM Width; Needle Roller Bearing; Roller Assembly Only; No Self Aligning; Retainer; Single Row of Rollers; No Separable
Manufacturer URL	http://www.koyousa.com
(Refer.)Mass(kg)	0.009
Manufacturer Name	KOYO
Weight / Kilogram	0.009
Bore Diameter (mm)	18
Outer Diameter (mm)	22
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.40.00.00
(Oil) Lubrication Speed	24000 r/min
Manufacturer Item Number	K18X22X17H
Number of Rows of Rollers	Single Row
(Grease) Lubrication Speed	16000 r/min
Basic static load rating (C0)	19.9 kN
Basic dynamic load	13.3 kN



rating (C)	
------------	--