



Bearing No. B7210-E-2RSD-T-P4S

|                     |                                                     |
|---------------------|-----------------------------------------------------|
| D                   | 90 mm                                               |
| d                   | 50 mm                                               |
| B                   | 20 mm                                               |
| a                   | 26 mm                                               |
| m                   | 0,465 kg / Weight                                   |
| ?                   | 25 ° / Angle                                        |
| Size (mm)           | 50x90x20                                            |
| Width (mm)          | 20                                                  |
| d <sub>a</sub>      | 57 mm / Tolerance: h12                              |
| C <sub>r</sub>      | 41000 N / Dynamic load rating (radial)              |
| D <sub>a</sub>      | 83 mm / Tolerance: H12                              |
| C <sub>0r</sub>     | 21400 N / Static load rating (radial)               |
| Bearing number      | B7210-E-2RSD-T-P4S                                  |
| r <sub>min</sub>    | 1,1 mm                                              |
| r <sub>a max</sub>  | 1 mm                                                |
| r <sub>1 min</sub>  | 1,1 mm                                              |
| r <sub>a1 max</sub> | 1 mm                                                |
| Bore Diameter (mm)  | 50                                                  |
| n <sub>G Fett</sub> | 14000 1/min / Limiting speed for grease lubrication |
| Outer Diameter (mm) | 90                                                  |