



Bearing No. 32926

a	34,7 mm
e	0.36
d	130 mm
D	180 mm
T	32 mm
B	30 mm
C	26 mm
Y1	1.7
Z_	30
D_	180
C0	281
Cr	17000
Sa	6
db	141
da	142
B_	30
Y0	0.92
Sb	6
C_	26
DA_	12.631
C0r	28600
DI_	144.205
DE_	168.242
Iso	-
D_b	175
Noun	Bearing
D_a1	171
Bore	5.118 Inch 130 Millimeter
mass	2.25

SDM_	156.224
SBRG	29
D_a2	168
KBRG	3111
yobi	32926
TC-RA	371.854
ALPHA_	13.5
LangID	1
Weight	2,25 Kg
Da min	168 mm
TC-DA1	12.979
TC-DA2	12.283
UNSPSC	31171516
TC-SLR	20
r min.	2 mm
T-ALP23	0
inner r	2
T-ALP21	27
r1 min.	1,5 mm
T-ALP22	0
Da max.	171 mm
GRS rpm	1800
db max.	141 mm
da min.	142 mm
Db min.	175 mm
outer r	1.5
rb max.	1,5 mm
hidYobi	32926
Oil rpm	2400
ra max.	2 mm
outer rb	1.5
hidTable	ecat_NSTPRM

TC-BET21	2
Category	Tapered Roller Bearings Assembly
TC-BET23	0
inner ra	2
TC-BET22	0
Size (mm)	130x180x32
Inventory	0.0
Component	Assembly
Prod_Type3	TRBSR_MD_A
Width (mm)	32
Weight / LBS	4.96
Basic Number	32926
Product Group	B04334
Inch - Metric	Metric
Bearing number	32926
Assembly Width	1.26 Inch 32 Millimeter
Other Features	Standard Angle Pressed Steel Cage
Keyword String	Tapered
Precision Class	Standard
Long Description	Assembly; Standard Precision; 130MM Bore; 180MM Outside Diameter; 32MM Assembly Width; Single Row of Rollers
Outside Diameter	7.087 Inch 180 Millimeter
Manufacturer URL	http://www.nskamericas.com
Weight / Kilogram	2.25
Manufacturer Name	NSK
Bore Diameter (mm)	130
Outer Diameter (mm)	180

Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.20.00.00
Number of Tapered Rows	Single Row
Calculation factor (e)	0,36
Flange Outside Diameter	0 Inch 0 Millimeter
Calculation factor (Y0)	0,92
(Oil) Lubrication Speed	2400 r/min
Manufacturer Item Number	32926
(Grease) Lubrication Speed	1800 r/min
Basic static load rating (C0)	281 kN
Basic dynamic load rating (C)	167 kN