



Bearing No. B7016-C-T-P4S

|                     |                                                                   |
|---------------------|-------------------------------------------------------------------|
| D                   | 125 mm                                                            |
| d                   | 80 mm                                                             |
| B                   | 22 mm                                                             |
| a                   | 25 mm                                                             |
| m                   | 0,836 kg / Weight                                                 |
| ?                   | 15 ° / Angle                                                      |
| Size (mm)           | 80x125x22                                                         |
| Width (mm)          | 22                                                                |
| d <sub>a</sub>      | 88 mm / Tolerance: h12                                            |
| C <sub>r</sub>      | 64000 N / Dynamic load rating (radial)                            |
| D <sub>a</sub>      | 117 mm / Tolerance: H12                                           |
| C <sub>0r</sub>     | 41000 N / Static load rating (radial)                             |
| Bearing number      | B7016-C-T-P4S                                                     |
| r <sub>min</sub>    | 1,1 mm                                                            |
| n <sub>G Ol</sub>   | 17000 1/min / Limiting speed for minimal quantity oil lubrication |
| r <sub>a max</sub>  | 1 mm                                                              |
| r <sub>1 min</sub>  | 1,1 mm                                                            |
| r <sub>a1 max</sub> | 0,6 mm                                                            |
| Bore Diameter (mm)  | 80                                                                |
| n <sub>G Fett</sub> | 11000 1/min / Limiting speed for grease lubrication               |
| Outer Diameter (mm) | 125                                                               |