



Bearing No. B7000-C-2RSD-T-P4S

|                     |                                                     |
|---------------------|-----------------------------------------------------|
| D                   | 26 mm                                               |
| d                   | 10 mm                                               |
| B                   | 8 mm                                                |
| a                   | 6 mm                                                |
| m                   | 0,021 kg / Weight                                   |
| ?                   | 15 ° / Angle                                        |
| Size (mm)           | 10x26x8                                             |
| Width (mm)          | 8                                                   |
| d <sub>a</sub>      | 14 mm / Tolerance: h12                              |
| C <sub>r</sub>      | 4100 N / Dynamic load rating (radial)               |
| D <sub>a</sub>      | 22 mm / Tolerance: H12                              |
| C <sub>0r</sub>     | 1470 N / Static load rating (radial)                |
| Bearing number      | B7000-C-2RSD-T-P4S                                  |
| r <sub>min</sub>    | 0,3 mm                                              |
| r <sub>a max</sub>  | 0,3 mm                                              |
| r <sub>1 min</sub>  | 0,3 mm                                              |
| r <sub>a1 max</sub> | 0,1 mm                                              |
| Bore Diameter (mm)  | 10                                                  |
| n <sub>G Fett</sub> | 67000 1/min / Limiting speed for grease lubrication |
| Outer Diameter (mm) | 26                                                  |