




Bearing No. 708/600 AGMB

a	212 mm
d	600 mm
D	730 mm
B	42 mm
Size (mm)	730x600x42
Width (mm)	42
Mass bearing	38.5 kg
d ₁	643.55 mm
D ₁	676.9 mm
Limiting speed	850 r/min
Bearing number	708/600 AGMB
Reference speed	800 r/min
d _a min.	613 mm
D _a max.	717 mm
D _b max.	724 mm
Bore Diameter (mm)	730
r _a max.	2.5 mm
r _b max.	1 mm
Outer Diameter (mm)	600
r _{3,4} min.	1.1 mm
r _{1,2} min.	3 mm
Calculation factor A	4.87
Calculation factor e	0.8
Calculation factor X	0.63
r _b - max.	1 mm
r _a - max.	2.5 mm
D _b - max.	724 mm
D _a - max.	717 mm
d _a - min.	613 mm
D ₁ ?	676.9 mm

d_1 ?	643.55 mm
$r_{1,2}$ - min.	3 mm
$r_{3,4}$ - min.	1.1 mm
Calculation factor - X	0.39
Calculation factor - e	0.8
Basic dynamic load rating C	338 kN
Basic dynamic load rating - C	338 kN
Calculation factor k_r	0.078
Calculation factor Y_0	0.66
Calculation factor Y_2	1.24
Calculation factor Y_1	0.78
Fatigue load limit P_u	14 kN
Calculation factor - Y_0	0.33
Calculation factor - Y_1	
Calculation factor - k_a	0.2
Calculation factor - k_r	0.078
Calculation factor - Y_2	0.76
Fatigue load limit - P_u	14 kN
Basic static load rating C_0	735 kN
Basic static load rating - C_0	735 kN