



Bearing No. 61900

D	22 mm
d	10 mm
B	6 mm
C	6 mm
D1	18,2 mm
D2	– mm
d1	13,9 mm
Noun	Bearing
Bore	0.394 Inch 10 Millimeter
UNSPSC	31171504
Weight	0,01 Kg
rc max.	0,3 mm
Da max.	20 mm
da min.	12 mm
r2 min.	0,3 mm
r1 min.	0,3 mm
series:	61
Category	Single Row Ball Bearing
Inventory	0.0
Snap Ring	No
Size (mm)	10x22x6
Enclosure	Open
Width (mm)	6
bore type:	Round
Mass bearing	0.01 kg
Weight / LBS	0.02
maximum rpm:	45000 RPM
Product Group	B00308
Inch - Metric	Metric

closure type:	Open
Cage Material	Steel
Keyword String	Ball
bore diameter:	10 mm
overall width:	6 mm
cage material:	Steel
fillet radius:	0.3 mm
Bearing number	61900
Limiting speed	45000 r/min
finish/coating:	Uncoated
Rolling Element	Ball Bearing
Reference speed	70000 r/min
Precision Class	ABEC 1 ISO P0
Outside Diameter	0.866 Inch 22 Millimeter
Outer Race Width	0.236 Inch 6 Millimeter
Long Description	10MM Bore; 22MM Outside Diameter; 6MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	http://www.skf.com
Manufacturer Name	SKF
Weight / Kilogram	0.011
outer ring width:	6 mm
outside diameter:	22 mm
precision rating:	Not Rated
d _a min.	12 mm
D _a max.	20 mm
r _a max.	0.3 mm
Bore Diameter (mm)	10
Internal Clearance	C0-Medium

Outer Diameter (mm)	22
internal clearance:	C0
snap ring included:	Without Snap Ring
$r_{1,2}$ min.	0.3 mm
Minimum Buy Quantity	N/A
static load capacity:	1.27 kN
D_1 ?	18.2 mm
d_1 ?	13.9 mm
row type & fill slot:	Single Row Non-Fill Slot
dynamic load capacity:	2.7 kN
Harmonized Tariff Code	8482.10.50.68
Fatigue load limit (Pu)	0,054
Calculation factor (f0)	14
Manufacturer Item Number	61900
Internal Special Features	No
Basic dynamic load rating C	2.7 kN
Basic dynamic load rating (C)	2,7 kN
Basic static load rating (C0)	1,27 kN
Maximum Capacity / Filling Slot	No
Fatigue load limit P_u	0.054 kN
Calculation factor k_r	0.02
Calculation factor f_0	14
Basic static load rating C_0	1.27 kN