



Bearing No. BT4B 328828 G/HA1

D	438.048 mm
d	304.648 mm
B	280.99 mm
T	279.4 mm
?	15 °
?	15 °
Size (mm)	438.048x304.648x280.99
Width (mm)	280,99
Mass bearing	135 kg
Bearing number	BT4B 328828 G/HA1
Thrust factor K	1.24
Thrust factor - K	1.24
Bore Diameter (mm)	438,048
Outer Diameter (mm)	304,648
r _{1,2} min.	2 mm
r _{3,4} min.	4.8 mm
Calculation factor e	0.48
D ₁ ?	385 mm
d ₁ ?	337 mm
Design variant/feature	TQO/GWI
r _{1,2} - min.	2 mm
r _{3,4} - min.	4.8 mm
Calculation factor - e	0.48
Basic dynamic load rating C	3080 kN
Basic dynamic load rating - C	3080 kN
Fatigue load limit P _u	585 kN
Calculation factor Y ₂	2.1
Calculation factor Y ₁	1.4

Calculation factor Y_0	1.4
Calculation factor - Y_0	1.4
Calculation factor - Y_2	2.1
Fatigue load limit - P_u	585 kN
Calculation factor - Y_1	1.4
Basic static load rating C_0	6950 kN
Basic static load rating - C_0	6950 kN
Comparative radial load rating C_F	815 kN
Comparative axial load rating C_{Fa}	190 kN
Comparative axial load rating - C_{Fa}	190 kN
Comparative radial load rating - C_F	815 kN