



**Bearing No. K25X32X16**

Fw	25 mm
Ew	33 mm
Bc	16 mm
Cr	19.8
Cu	4.00
P/S	S
C0r	25.3
Noun	Bearing
Bore	0.984 Inch   25 Millimeter
Width	0.63 Inch   16 Millimeter
UNSPSC	31171512
Weight	0.027 Kg
Retainer	Yes
Oil lub.	18000
Category	Needle Non Thrust Roller Bearing
Inventory	0.0
Separable	No
Component	Roller Assembly Only
Enclosure	Not Applicable
Closed End	Not Applicable
Grease lub.	12000
Bearing No.	K25X32X16
Shaft(max.)	25.000
Shaft(min.)	24.991
Weight / LBS	0.06
Housing(max.)	32.025
Housing(min.)	32.009
Inch - Metric	Metric
Product Group	B04144

Self Aligning	No
Other Features	Radial Roller   Steel Cage
Bearing number	K25X32X16
Keyword String	Needle
Thrust Bearing	No
Rolling Element	Needle Roller Bearing
Outside Diameter	1.26 Inch   32 Millimeter
Long Description	25MM Bore; 32MM Outside Diameter; 16MM Width; Needle Roller Bearing; Roller Assembly Only; No Self Aligning; Retainer; Single Row of Rollers; No Separable
Manufacturer URL	<a href="http://www.koyousa.com">http://www.koyousa.com</a>
(Refer.)Mass(kg)	0.027
Manufacturer Name	KOYO
Weight / Kilogram	0.03
Bore Diameter (mm)	25
Outer Diameter (mm)	33
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.40.00.00
(Oil) Lubrication Speed	18000 r/min
Manufacturer Item Number	K25X32X16
Number of Rows of Rollers	Single Row
(Grease) Lubrication Speed	12000 r/min
Basic static load rating (C0)	25.3 kN
Basic dynamic load rating (C)	19.8 kN