




Bearing No. BT2B 334045/HA3

h	11.7 mm
d	390 mm
D	568 mm
T	180 mm
B	180 mm
b	32 mm
Size (mm)	568x390x180
Width (mm)	180
Mass bearing	155 kg
Bearing number	BT2B 334045/HA3
Thrust factor K	0.7
Thrust factor - K	0.7
Bore Diameter (mm)	568
Outer Diameter (mm)	390
Calculation factor e	0.83
$r_{3,4}$ min.	5 mm
$r_{1,2}$ min.	2 mm
d_1 ?	412 mm
D_1 ?	470 mm
$r_{3,4}$ - min.	5 mm
Design variant/feature	TDIS.2/N1
$r_{1,2}$ - min.	2 mm
Calculation factor - e	0.83
Basic dynamic load rating C	2550 kN
Basic dynamic load rating - C	2380 kN
Calculation factor Y_0	0.8
Calculation factor Y_2	1.2
Calculation factor Y_1	0.81
Fatigue load limit P_u	455 kN

Calculation factor - Y_0	0.8
Calculation factor - Y_2	1.2
Fatigue load limit - P_u	450 kN
Calculation factor - Y_1	0.81
Basic static load rating C_0	5850 kN
Basic static load rating - C_0	5850 kN
Comparative radial load rating C_F	630 kN
Comparative axial load rating C_{Fa}	514 kN
Comparative radial load rating - C_F	585 kN
Comparative axial load rating - C_{Fa}	479 kN