



Bearing No. BT2B 332493/HA4

a	620 mm
d	635 mm
D	990.6 mm
T	339.725 mm
C	212.725 mm
Size (mm)	990.6x635x339.725
Width (mm)	339,725
Mass bearing	840 kg
Bearing number	BT2B 332493/HA4
Thrust factor K	0.67
Thrust factor - K	0.67
Bore Diameter (mm)	990,6
Outer Diameter (mm)	635
Calculation factor e	0.88
$r_{3,4}$ min.	6.4 mm
$r_{1,2}$ min.	6.4 mm
$d_1$ ?	810 mm
$D_1$ ?	960 mm
$r_{1,2}$ - min.	6.4 mm
Design variant/feature	TDOS.1/D3
$r_{3,4}$ - min.	6.4 mm
Calculation factor - e	0.88
Basic dynamic load rating C	8090 kN
Basic dynamic load rating - C	8090 kN
Fatigue load limit $P_u$	1060 kN
Calculation factor $Y_0$	0.8
Calculation factor $Y_2$	1.15
Calculation factor $Y_1$	0.77
Calculation factor - $Y_0$	0.8

Calculation factor - $Y_1$	0.77
Calculation factor - $Y_2$	1.15
Fatigue load limit - $P_u$	1060 kN
Basic static load rating $C_0$	16000 kN
Basic static load rating - $C_0$	16000 kN
Comparative radial load rating $C_F$	2000 kN
Comparative axial load rating $C_{Fa}$	1730 kN
Comparative radial load rating - $C_F$	2000 kN
Comparative axial load rating - $C_{Fa}$	1730 kN