



Bearing No. A4050/A4138

e	0.45
d	12,7 mm
D	34,988 mm
T	10,998 mm
B	10,988 mm
C	8,73 mm
a	8,2 mm
Da	29 mm
B_	10.988
Db	32 mm
da	18,5 mm
Y0	0.73
db	17 mm
C0	10.9
D_	34.988
Z_	12
C_	8.73
Y1	1.3
DE_	28.368
SLR	7
D_a	29
DI_	19.841
DA1	4.552
DA2	3.945
CUP	0.022
DA_	4.25
D_b	32
RAr	52.176
SDM_	24.018
KBRG	3161

yobi	A4050/A4138
CONE	0.033
ALP21	33
ALP22	34
ALP23	0
BETA_	2
BET21	5
BET23	0
BET22	0
r min.	1,3 mm
LangID	1
Weight	0,055 Kg
ALPHA_	16.783
r1 min.	1,3 mm
ra max.	1,3 mm
Oil rpm	16000
outer r	1.3
hidYobi	A4050/A4138
GRS rpm	12000
inner r	1.3
hidTable	ecat_NSTPRI
inner ra	1.3
outer rb	1.3
ra1 max.	1,3 mm
Size (mm)	12.7x34.988x10.998
SHOG_yobi	A4050/A4138
Prod_Type3	TRBSR_ID_A
Width (mm)	10,998
Bearing number	A4050/A4138
Bore Diameter (mm)	12,7
Outer Diameter (mm)	34,988
Calculation factor (e)	0,45

(Oil) Lubrication Speed	16000 r/min
Calculation factor (Y0)	0,73
(Grease) Lubrication Speed	12000 r/min
Basic static load rating (C0)	10,9 kN
Basic dynamic load rating (C)	11,7 kN