



Bearing No. K32X39X18H

Fw	32 mm
Ew	40 mm
Bc	18 mm
Cr	25.8
Cu	6.05
P/S	S
C0r	38.2
Noun	Bearing
Bore	1.26 Inch 32 Millimeter
Width	0.709 Inch 18 Millimeter
UNSPSC	31171512
Weight	0.033 Kg
Retainer	Yes
Oil lub.	14000
Category	Needle Non Thrust Roller Bearing
Inventory	0.0
Separable	No
Component	Roller Assembly Only
Enclosure	Not Applicable
Closed End	Not Applicable
Grease lub.	8900
Bearing No.	K32X39X18H
Shaft(max.)	32.000
Shaft(min.)	31.989
Weight / LBS	0.073
Housing(max.)	39.025
Housing(min.)	39.009
Inch - Metric	Metric
Product Group	B04144

Self Aligning	No
Other Features	Radial Roller Hardened Steel Cage
Bearing number	K32X39X18H
Keyword String	Needle
Thrust Bearing	No
Rolling Element	Needle Roller Bearing
Outside Diameter	1.535 Inch 39 Millimeter
Long Description	32MM Bore; 39MM Outside Diameter; 18MM Width; Needle Roller Bearing; Roller Assembly Only; No Self Aligning; Retainer; Single Row of Rollers; No Separable
Manufacturer URL	http://www.koyousa.com
(Refer.)Mass(kg)	0.033
Manufacturer Name	KOYO
Weight / Kilogram	0.03
Bore Diameter (mm)	32
Outer Diameter (mm)	40
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.40.00.00
(Oil) Lubrication Speed	14000 r/min
Manufacturer Item Number	K32X39X18H
Number of Rows of Rollers	Single Row
(Grease) Lubrication Speed	8900 r/min
Basic static load rating (C0)	38.2 kN
Basic dynamic load rating (C)	25.8 kN