



Bearing No. 62/32DDU

r	1
d	32 mm
D	65 mm
B	17 mm
C	17 mm
fo	13.6
D_	65
B_	17
ra	1
Z_	8
C0	11.6
DI_	38.181
SRE	5.47
D_a	60
DE_	58.819
SRI	5.21
DA_	10.319
SREN	0
Bore	1.26 Inch 32 Millimeter
SRIN	0
bomp	0
SRIX	0.025
yobi	62/32DDU
mass	0.225
SDM_	48.5
KBRG	6161
SREX	0.05
SBRG	2
Noun	Bearing
da max	40 mm

Weight	0,225 Kg
LangID	1
r min.	1 mm
da min	37
ALPHA_	0
C_conv	20700
UNSPSC	31171504
da min.	37 mm
hidYobi	62/32DDU
GRS rpm	7100
Da max.	60 mm
ra max.	1 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Snap Ring	No
Enclosure	2 Seals
Size (mm)	32x65x17
Inventory	0.0
Prod_Type3	DGBB_SR_DD
Width (mm)	17
Weight / LBS	0.4961
Product Group	B00308
Inch - Metric	Metric
Cage Material	Steel
Bearing number	62/32DDU
Enclosure Type	Contact Seal
Other Features	Deep Groove Rubber Seal
Keyword String	Ball
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Inner Race Width	0 Inch 0 Millimeter
Outside Diameter	2.559 Inch 65

	Millimeter
Long Description	32MM Bore; 65MM Outside Diameter; 17MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage;
Manufacturer URL	http://www.nskamericas.com
Outer Race Width	0.669 Inch 17 Millimeter
Weight / Kilogram	0.22
Manufacturer Name	NSK
Internal Clearance	C0-Medium
Bore Diameter (mm)	32
Outer Diameter (mm)	65
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Internal Special Features	No
(Grease) Lubrication Speed	7 100 r/min
Basic dynamic load rating (C)	20,7 kN
Basic static load rating (C0)	11,6 kN
Maximum Capacity / Filling Slot	No