




Bearing No. 62/32NR

f	1,65 mm
d	32 mm
D	65 mm
B	17 mm
C	17 mm
a	3,28 mm
b	2,05 mm
Cr	29.4
f0	13.3
Cu	0.990
D2	70,7 mm
D1	62,6 mm
C0r	13.1
Bore	1.26 Inch 32 Millimeter
Noun	Bearing
r min.	1 mm
r(min)	1
UNSPSC	31171504
Weight	0,228 Kg
r1(min)	0.5
da(min)	37
D2(min)	70.7
Da(max)	60
rb(max)	0.5
ra(max)	1
Dx(min)	71.5
r0 max.	0,6 mm
r1 min.	0,5 mm
da min.	37 mm
Cy(max)	4.67

Da max.	60 mm
Category	Single Row Ball Bearing
Oil lub.	12000
Snap Ring	Yes
Size (mm)	32x65x17
Inventory	0.0
Enclosure	Open
Width (mm)	17
Grease lub.	10000
f{0.05)	1.65
Bearing No.	62/32NR
Weight / LBS	0.50265
Cage Material	Steel
Inch - Metric	Metric
Product Group	B00308
Bearing number	62/32NR
Other Features	Deep Groove With Snap Ring
Keyword String	Ball
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Manufacturer URL	http://www.koyousa.com
Outer Race Width	0.669 Inch 17 Millimeter
(Refer.)Mass(kg)	0.228
Long Description	32MM Bore; 65MM Outside Diameter; 17MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; Yes Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Inner Race Width	0 Inch 0 Millimeter

Outside Diameter	2.559 Inch 65 Millimeter
Weight / Kilogram	0.247
Manufacturer Name	KOYO
Internal Clearance	C0-Medium
Bore Diameter (mm)	32
Outer Diameter (mm)	65
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	12000 r/min
Internal Special Features	No
(Grease) Lubrication Speed	10000 r/min
Basic static load rating (C0)	13,1 kN
Basic dynamic load rating (C)	23,5 kN
Maximum Capacity / Filling Slot	No