




Bearing No. NA4912R

k	3 mm
C	25 mm
s	1,5 mm
d	60 mm
F	68 mm
D	85 mm
B	25 mm
Lw	18.8 mm
Dw	5.5 mm
Cr	61.5 kN
C0r	108 kN
Mass	0.43 kg
s max	1.5 mm
r min.	1 mm
Da max	80 mm
da min	65 mm
rs min	1 mm
Weight	0,427 Kg
ras max	1 mm
Da max.	80 mm
da min.	65 mm
ra max.	1 mm
Category	Roller Bearings
Inventory	0.0
Size (mm)	60x85x25
Width (mm)	25
Nlim (oil)	6,000 rpm
Nlim (grease)	4,000 rpm
Product Group	B04144
Bearing number	NA4912R

Precision class	P0
Weight / Kilogram	0.428
Manufacturer Name	NTN
Bore Diameter (mm)	60
Outer Diameter (mm)	85
Minimum Buy Quantity	N/A
Radial clearance class	CN
(Grease) Lubrication Speed	4 000 r/min
Basic static load rating (C0)	108 kN
Basic dynamic load rating (C)	61,5 kN
Lubrication hole on inner ring	Non/No
Lubrication hole on outer ring	Oui/Yes
Max operating temperature, Tmax	120 °C
Min operating temperature, Tmin	-20 °C
Characteristic cage frequency, FTF	0.46 Hz
Characteristic outer ring frequency, BPF0	12.95 Hz
Characteristic inner ring frequency, BPF1	15.05 Hz
Characteristic rolling element frequency, BSF	13.29 Hz