



Bearing No. 6200DDU

r	0.6
d	10 mm
D	30 mm
B	9 mm
C	9 mm
D_	30
C0	2.39
Z_	8
ra	0.6
fo	13.2
B_	9
DI_	15.738
SRI	2.46
DE_	25.262
SRE	2.52
DA_	4.762
D_a	26
KBRG	6161
SBRG	2
SRIN	-0.015
bomp	0
SREX	0.03
yobi	6200DDU
SRIX	0.015
mass	0.032
SDM_	20.5
SREN	0
Bore	0.394 Inch 10 Millimeter
Noun	Bearing

LangID	1
UNSPSC	31171504
da min	14
r min.	0,6 mm
Weight	0,032 Kg
ALPHA_	0
C_conv	5100
da max	16 mm
GRS rpm	18000
Da max.	26 mm
ra max.	0,6 mm
da min.	14 mm
hidYobi	6200DDU
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Size (mm)	10x30x9
Enclosure	2 Seals
Snap Ring	No
Inventory	0.0
Width (mm)	9
Prod_Type3	DGBB_SR_DD
Weight / LBS	0.06556
Inch - Metric	Metric
Product Group	B00308
Cage Material	Steel
Bearing number	6200DDU
Keyword String	Ball
Other Features	Deep Groove Rubber Seal
Enclosure Type	Contact Seal
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Inner Race Width	0 Inch 0 Millimeter

Outside Diameter	1.181 Inch 30 Millimeter
Long Description	10MM Bore; 30MM Outside Diameter; 9MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage; C
Manufacturer URL	http://www.nskamericas.com
Outer Race Width	0.354 Inch 9 Millimeter
Manufacturer Name	NSK
Weight / Kilogram	0.032
Internal Clearance	C0-Medium
Bore Diameter (mm)	10
Outer Diameter (mm)	30
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6200DDU
Internal Special Features	No
(Grease) Lubrication Speed	18 000 r/min
Basic static load rating (C0)	2,39 kN
Basic dynamic load rating (C)	5,1 kN
Maximum Capacity / Filling Slot	No