




Bearing No. 6201 N

D	32 mm
d	12 mm
B	10 mm
b	1.35 mm
C	2.06 mm
Size (mm)	32x12x10
Width (mm)	10
Mass bearing	0.037 kg
D ₃	30.15 mm
d ₁	18.45 mm
D ₂	27.34 mm
D ₃	30.15 mm
r ₀	0.4 mm
Limiting speed	32000 r/min
Bearing number	6201 N
Reference speed	50000 r/min
Bore Diameter (mm)	32
r _a max.	0.6 mm
C _a max.	3.18 mm
b _a min.	1.5 mm
D _b min.	38 mm
D _a max.	27.8 mm
d _a min.	16.2 mm
r ₀ max.	0.4 mm
Outer Diameter (mm)	12
D _a - max.	27.8 mm
r _{1,2} min.	0.6 mm
d _a - min.	16.2 mm
C _a - max.	3.18 mm

r_a - max.	0.6 mm
D_b - min.	38 mm
b_a - min.	1.5 mm
D_2 ?	27.34 mm
d_1 ?	18.45 mm
$r_{1,2}$ - min.	0.6 mm
Basic dynamic load rating C	7.28 kN
Basic dynamic load rating - C	7.3 kN
Fatigue load limit P_u	0.132 kN
Calculation factor k_r	0.025
Calculation factor f_0	12
Fatigue load limit - P_u	0.132 kN
Calculation factor - k_r	0.025
Calculation factor - f_0	12
Basic static load rating C_0	3.1 kN
Basic static load rating - C_0	3.1 kN