



Bearing No. 6201DDU

r	0.6
d	12 mm
D	32 mm
B	10 mm
C	10 mm
D_	32
C0	3.05
Z_	7
ra	0.6
fo	12.3
B_	10
DI_	16.047
SRI	3.01
DE_	27.953
SRE	3.16
DA_	5.953
D_a	28
KBRG	6161
SBRG	2
SRIN	0
bomp	0
SREX	0.03
yobi	6201DDU
SRIX	0.015
mass	0.037
SDM_	22
SREN	0
Bore	0.472 Inch 12 Millimeter
Noun	Bearing

LangID	1
UNSPSC	31171504
da min	16
r min.	0,6 mm
Weight	0,037 Kg
ALPHA_	0
C_conv	6800
da max	17 mm
GRS rpm	17000
Da max.	28 mm
ra max.	0,6 mm
da min.	16 mm
hidYobi	6201DDU
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Size (mm)	12x32x10
Enclosure	2 Seals
Snap Ring	No
Inventory	0.0
Width (mm)	10
Prod_Type3	DGBB_SR_DD
Weight / LBS	0.08014
Inch - Metric	Metric
Product Group	B00308
Cage Material	Steel
Bearing number	6201DDU
Keyword String	Ball
Other Features	Deep Groove Rubber Seal
Enclosure Type	Contact Seal
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outer Race Width	0.394 Inch 10

	Millimeter
Inner Race Width	0 Inch 0 Millimeter
Long Description	12MM Bore; 32MM Outside Diameter; 10MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage;
Manufacturer URL	http://www.nskamericas.com
Outside Diameter	1.26 Inch 32 Millimeter
Manufacturer Name	NSK
Weight / Kilogram	0.038
Internal Clearance	C0-Medium
Bore Diameter (mm)	12
Outer Diameter (mm)	32
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6201DDU
Internal Special Features	No
(Grease) Lubrication Speed	17 000 r/min
Basic static load rating (C0)	3,05 kN
Basic dynamic load rating (C)	6,8 kN
Maximum Capacity / Filling Slot	No