



Bearing No. 6201LLU

C	10 mm
d	12 mm
D	32 mm
B	10 mm
Noun	Bearing
Bore	0.472 Inch 12 Millimeter
da max	17 mm
UNSPSC	31171504
Weight	0,037 Kg
r min.	0,6 mm
da min.	16 mm
Da max.	28 mm
ra max.	0,6 mm
Category	Single Row Ball Bearing
Enclosure	2 Seals
Size (mm)	12x32x10
Inventory	0.0
Snap Ring	No
Width (mm)	10
bore type:	Round
Weight / LBS	0.082
closure type:	Double Sealed
Inch - Metric	Metric
Cage Material	Steel
Product Group	B00308
Keyword String	Ball
overall width:	10 mm
bore diameter:	12 mm
Enclosure Type	Contact Seal

Bearing number	6201LLU
fillet radius:	0.6 mm
cage material:	Steel
Rolling Element	Ball Bearing
finish/coating:	Uncoated
Reference speed	16 000 r/min
Precision Class	ABEC 1 ISO P0
Long Description	12MM Bore; 32MM Outside Diameter; 10MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	http://www.ntnamerica.com
Outer Race Width	0.394 Inch 10 Millimeter
Outside Diameter	1.26 Inch 32 Millimeter
Weight / Kilogram	0.037
Manufacturer Name	NTN
bearing material:	High Carbon Chrome Steel
outside diameter:	32 mm
inner ring width:	10 mm
outer ring width:	10 mm
precision rating:	ISO Class 0
Internal Clearance	C0-Medium
Bore Diameter (mm)	12
snap ring included:	Without Snap Ring
Outer Diameter (mm)	32
internal clearance:	CN
Minimum Buy Quantity	N/A
static load capacity:	2750 N

maximum rpm (grease):	16000 rpm
row type & fill slot:	Single Row Non-Fill Slot
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	6100 N
Manufacturer Item Number	6201LLU
Internal Special Features	No
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Basic static load rating (C0)	2,75 kN
Basic dynamic load rating (C)	6,1 kN
Maximum Capacity / Filling Slot	No