




Bearing No. 6201ZZE

D	32 mm
d	12 mm
B	10 mm
C	10 mm
Noun	Bearing
Bore	0.472 Inch 12 Millimeter
Width	10 mm
UNSPSC	31171504
r min.	0.6 mm
Weight	0.037 Kg
da min.	17 mm
Da max.	27 mm
ra max.	0.6 mm
Category	Single Row Ball Bearing
ra (max)	0.6 mm
da (min)	17 mm
Da (max)	27 mm
Size (mm)	12x32x10
Snap Ring	No
Enclosure	2 Metal Shields
Bore Size	12 mm
Bore Type	Cylindrical Bore
Inventory	0.0
Factor fo	12.3
Width (mm)	10
Weight / LBS	0.081
Product Group	B00308
Configuration	Single Row
Cage Material	Steel

Inch - Metric	Metric
Keyword String	Ball
Other Features	Deep Groove
Bearing number	6201ZZE
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Long Description	12MM Bore; 32MM Outside Diameter; 10MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Stee
Outer Race Width	0.394 Inch 10 Millimeter
Radial Clearance	0.003 to 0.018 mm
Outside Diameter	1.26 Inch 32 Millimeter
Manufacturer URL	http://www.nachiamerica.com
Inner Race Width	0 Inch 0 Millimeter
Manufacturer Name	NACHI
Weight / Kilogram	0
Internal Clearance	C0-Medium
Static Load Rating	3,050 N
Bore Diameter (mm)	12
Dynamic Load Rating	6,800 N
Outer Diameter (mm)	32
Minimum Buy Quantity	N/A
Fillet Radius/Chamfer	0.6 mm
Harmonized Tariff Code	8482.10.50.68
Limiting Speed - Grease	22,000 rpm
Internal Special Features	No

(Grease) Lubrication Speed	22000 r/min
Basic static load rating (C0)	3,05 kN
Basic dynamic load rating (C)	6,8 kN
Maximum Capacity / Filling Slot	No