



Bearing No. 6202

C	11 mm
d	15 mm
D	35 mm
B	11 mm
Bore	0.591 Inch 15 Millimeter
Noun	Bearing
Width	11 mm
Weight	0.045 Kg
r min.	0.6 mm
UNSPSC	31171504
da min.	20 mm
Da max.	30 mm
ra max.	0.6 mm
da (min)	20 mm
Da (max)	30 mm
Category	Single Row Ball Bearing
ra (max)	0.6 mm
Bore Type	Cylindrical Bore
Enclosure	Open
Factor fo	13.1
Inventory	0.0
Bore Size	15 mm
Size (mm)	15x35x11
Snap Ring	No
Width (mm)	11
Weight / LBS	0.099
Configuration	Single Row
Inch - Metric	Metric
Cage Material	Steel

Product Group	B00308
Bearing number	6202
Other Features	Deep Groove
Keyword String	Ball
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Radial Clearance	0.003 to 0.018 mm
Outside Diameter	1.378 Inch 35 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	0.433 Inch 11 Millimeter
Long Description	15MM Bore; 35MM Outside Diameter; 11MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Manufacturer URL	http://www.nachi-america.com
Weight / Kilogram	0
Manufacturer Name	NACHI
Static Load Rating	3,700 N
Bore Diameter (mm)	15
Internal Clearance	C0-Medium
Outer Diameter (mm)	35
Dynamic Load Rating	7,650 N
Minimum Buy Quantity	N/A
Limiting Speed - Oil	24,000 rpm
Fillet Radius/Chamfer	0.6 mm
Harmonized Tariff Code	8482.10.50.68
Limiting Speed - Grease	20,000 rpm

Internal Special Features	No
(Grease) Lubrication Speed	19000 r/min
Basic dynamic load rating (C)	7,65 kN
Basic static load rating (C0)	3,7 kN
Maximum Capacity / Filling Slot	No