



### Bearing No. 6202

D	35 mm
d	15 mm
B	11 mm
C	11 mm
r	0.6
Z_	8
B_	11
D_	35
ra	0.6
C0	3.75
fo	13.2
DI_	19.547
SRI	3.01
D_a	31
DE_	31.453
DA_	5.953
SRE	3.16
SRIN	0
mass	0.045
Noun	Bearing
SRIX	0.015
SREN	0
Bore	0.591 Inch   15 Millimeter
KBRG	6101
SREX	0.03
bomp	0
SDM_	25.5
yobi	6202
SBRG	2

UNSPSC	31171504
LangID	1
r min.	0,6 mm
da min	19
C_conv	7650
ALPHA_	0
Weight	0,045 Kg
da max	20,5 mm
Da max.	31 mm
da min.	19 mm
Oil rpm	24000
ra max.	0,6 mm
GRS rpm	20000
hidYobi	6202
hidTable	ecat_NSRDGB
Category	Single Row Ball Bearing
Inventory	2.0
Size (mm)	15x35x11
Snap Ring	No
Enclosure	Open
Width (mm)	11
Prod_Type3	DGBB_SR_OT
Weight / LBS	0.1
Product Group	B00308
Inch - Metric	Metric
Cage Material	Steel
Bearing number	6202
Keyword String	Ball
Rolling Element	Ball Bearing
Precision Class	ABEC 1   ISO P0
Manufacturer URL	<a href="http://www.nskamericas.com">http://www.nskamericas.com</a>
Outer Race Width	0.433 Inch   11

	Millimeter
Outside Diameter	1.378 Inch   35 Millimeter
Long Description	15MM Bore; 35MM Outside Diameter; 11MM Outer Race Diameter; Open; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Weight / Kilogram	0.047
Manufacturer Name	NSK
Internal Clearance	C0-Medium
Bore Diameter (mm)	15
Outer Diameter (mm)	35
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	24 000 r/min
Manufacturer Item Number	6202
Internal Special Features	No
(Grease) Lubrication Speed	20 000 r/min
Basic static load rating (C0)	3,75 kN
Basic dynamic load rating (C)	7,65 kN
Maximum Capacity / Filling Slot	No