



**Bearing No. 6202-2Z**

C	11 mm
d	15 mm
D	35 mm
B	11 mm
d2	- mm
D2	0,6 mm
D1	30,4 mm
d1	21,7 mm
Noun	Bearing
Bore	0.591 Inch   15 Millimeter
UNSPSC	31171504
Weight	0,048 Kg
r1 min.	19,2 mm
r2 min.	19,2 mm
Da max.	30,8 mm
ra max.	0,6 mm
da min.	21,6 mm
Category	Single Row Ball Bearing
Snap Ring	No
Size (mm)	15x35x11
Inventory	0.0
Enclosure	2 Metal Shields
Width (mm)	11
Weight / LBS	0.099
Mass bearing	0.048 kg
Inch - Metric	Metric
Cage Material	Steel
Product Group	B00308
Other Features	Deep Groove

Keyword String	Ball
Bearing number	6202-2Z
Limiting speed	22000 r/min
Precision Class	ABEC 1   ISO P0
Rolling Element	Ball Bearing
Reference speed	43000 r/min
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Inner Race Width	0 Inch   0 Millimeter
Outer Race Width	0.433 Inch   11 Millimeter
Long Description	15MM Bore; 35MM Outside Diameter; 11MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Stee
Outside Diameter	1.378 Inch   35 Millimeter
Manufacturer Name	SKF
Weight / Kilogram	0.047
Internal Clearance	C0-Medium
$d_a$ max.	21.6 mm
$d_a$ min.	19.2 mm
$D_a$ max.	30.8 mm
Bore Diameter (mm)	15
$r_a$ max.	0.6 mm
Outer Diameter (mm)	35
$r_{1,2}$ min.	0.6 mm
Minimum Buy Quantity	N/A
$d_1$ ?	21.7 mm
$D_2$ ?	30.5 mm
Harmonized Tariff Code	8482.10.50.68

Calculation factor (f <sub>0</sub> )	13
Fatigue load limit (P <sub>u</sub> )	0,16
Manufacturer Item Number	6202-2Z
Internal Special Features	No
Basic dynamic load rating C	8.06 kN
Basic dynamic load rating (C)	8,06 kN
Basic static load rating (C <sub>0</sub> )	3,75 kN
Maximum Capacity / Filling Slot	No
Fatigue load limit P <sub>u</sub>	0.16 kN
Calculation factor k <sub>r</sub>	0.025
Calculation factor f <sub>0</sub>	13
Basic static load rating C <sub>0</sub>	3.75 kN