



Bearing No. NU1015

|            |           |
|------------|-----------|
| C          | 20 mm     |
| d          | 75 mm     |
| D          | 115 mm    |
| B          | 20 mm     |
| B2         | -         |
| Cu         | 10.2      |
| Ew         | -         |
| d1         | -         |
| B1         | -         |
| Cr         | 80.0      |
| Fw         | 85 mm     |
| C0r        | 78.1      |
| r min.     | 1.1 mm    |
| Weight     | 0.735 Kg  |
| r(min)     | 1.1       |
| da(min)    | -         |
| db(min)    | 80        |
| db(max)    | 83        |
| dc(min)    | -         |
| r1(min)    | 1         |
| dd(min)    | -         |
| Da(max)    | 108.5     |
| Db(max)    | -         |
| Db(min)    | -         |
| r1 min.    | 1 mm      |
| ra(max)    | 1         |
| rb(max)    | 1         |
| Oil lub.   | 6800      |
| Size (mm)  | 75x115x20 |
| Width (mm) | 20        |
|            |           |

|                               |            |
|-------------------------------|------------|
| Grease lub.                   | 5700       |
| Bearing No.                   | NU1015     |
| Bearing number                | NU1015     |
| (Refer.)Mass(kg)              | 0.735      |
| Bore Diameter (mm)            | 75         |
| Outer Diameter (mm)           | 115        |
| (Grease) Lubrication Speed    | 5700 r/min |
| Basic static load rating (C0) | 78.1 kN    |
| Basic dynamic load rating (C) | 63.6 kN    |