



VA201



2Z/VA201



2Z/VA208



2Z/VA228

### Bearing No. 6202-2Z/VA201

D	35 mm
d	15 mm
B	11 mm
C	11 mm
d1	21,7 mm
D2	30,4 mm
Noun	Bearing
Bore	0.591 Inch   15 Millimeter
Weight	0,045 Kg
UNSPSC	31171504
series:	62
r1 min.	0,6 mm
r2 min.	0,6 mm
Category	Single Row Ball Bearing
Snap Ring	No
Inventory	0.0
Size (mm)	15x35x11
Enclosure	2 Metal Shields
Width (mm)	11
bore type:	Round
Mass bearing	0.048 kg
Weight / LBS	0.099
maximum rpm:	360 RPM
Inch - Metric	Metric
Cage Material	Steel
Temperature -	30 to +250 °
Product Group	B00308
closure type:	Double Shielded
bore diameter:	15 mm

Limiting speed	180 r/min
overall width:	11 mm
fillet radius:	0.6 mm
cage material:	Steel
Bearing number	6202-2Z/VA201
Keyword String	Ball
Other Features	Deep Groove   Extreme Temperature Variant
finish/coating:	Uncoated
Rolling Element	Ball Bearing
Precision Class	ABEC 1   ISO P0
Long Description	15MM Bore; 35MM Outside Diameter; 11MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; Polyalkylene Glycol/Graphite Mixture Filled Internal Special Fea
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Outer Race Width	0.433 Inch   11 Millimeter
Outside Diameter	1.378 Inch   35 Millimeter
Inner Race Width	0 Inch   0 Millimeter
outer ring width:	11 mm
Weight / Kilogram	0.049
Manufacturer Name	SKF
outside diameter:	35 mm
precision rating:	Not Rated
Bore Diameter (mm)	15
Internal Clearance	C0-Medium
r <sub>a</sub> max.	0.6 mm

D <sub>a</sub> max.	30.8 mm
d <sub>a</sub> max.	21.6 mm
d <sub>a</sub> min.	19.2 mm
internal clearance:	C0
Outer Diameter (mm)	35
Minimum Buy Quantity	N/A
resistance features:	Corrosion Resistant, Extreme Temperature
r <sub>1,2</sub> min.	0.6 mm
D <sub>2</sub> ?	30.35 mm
static load capacity:	3.75 kN
d <sub>1</sub> ?	21.7 mm
row type & fill slot:	Single Row Non-Fill Slot
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6202-2Z/VA201
Internal Special Features	Polyalkylene Glycol/Graphite Mixture Filled
Basic dynamic load rating C	8.06 kN
Limiting temperature T max.	250 °C
operating temperature range:	-20 to +480 °F
Basic static load rating (C0)	3,75 kN
Maximum Capacity / Filling Slot	No
Basic static load rating C <sub>0</sub>	3.75 kN