



Bearing No. 6202-2Z/VA228

D	35 mm
d	15 mm
B	11 mm
C	11 mm
d1	21,7 mm
D2	30,4 mm
Noun	Bearing
Bore	0.591 Inch 15 Millimeter
Weight	0,045 Kg
UNSPSC	31171504
series:	62
r1 min.	0,6 mm
r2 min.	0,6 mm
Category	Single Row Ball Bearing
Snap Ring	No
Inventory	0.0
Size (mm)	15x35x11
Enclosure	2 Metal Shields
Width (mm)	11
bore type:	Round
Mass bearing	0.048 kg
Weight / LBS	0.099
maximum rpm:	360 RPM
Inch - Metric	Metric
Cage Material	Graphite
Temperature -	150 to +350 °
Product Group	B00308
closure type:	Double Shielded
bore diameter:	15 mm

Limiting speed	360 r/min
overall width:	11 mm
fillet radius:	0.6 mm
cage material:	Graphite
Bearing number	6202-2Z/VA228
Keyword String	Ball
Other Features	Deep Groove Extreme Temperature Variant
finish/coating:	Uncoated
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Long Description	15MM Bore; 35MM Outside Diameter; 11MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; Coronet Cage Internal Special Features; C0-Medium Internal Clear
Manufacturer URL	http://www.skf.com
Outside Diameter	1.378 Inch 35 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	0.433 Inch 11 Millimeter
outer ring width:	11 mm
Weight / Kilogram	0.05
Manufacturer Name	SKF
outside diameter:	35 mm
precision rating:	Not Rated
Bore Diameter (mm)	15
Internal Clearance	C0-Medium
r _a max.	0.6 mm
D _a max.	30.8 mm

d _a max.	21.6 mm
d _a min.	19.2 mm
internal clearance:	C0
Outer Diameter (mm)	35
Minimum Buy Quantity	N/A
resistance features:	Corrosion Resistant, Extreme Temperature
r _{1,2} min.	0.6 mm
D ₂ ?	30.35 mm
static load capacity:	3.75 kN
d ₁ ?	21.7 mm
row type & fill slot:	Single Row Non-Fill Slot
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6202-2Z/VA228
Internal Special Features	Coronet Cage
Basic dynamic load rating C	8.06 kN
Limiting temperature T max.	350 °C
operating temperature range:	-240 to +660 °F
Basic static load rating (C0)	3,75 kN
Maximum Capacity / Filling Slot	No
Basic static load rating C ₀	3.75 kN