



**Bearing No. 6202/VA201**

D	35 mm
d	15 mm
B	11 mm
C	11 mm
d1	21,7 mm
D2	30,4 mm
Noun	Bearing
Bore	0.591 Inch   15 Millimeter
Weight	0,045 Kg
UNSPSC	31171504
series:	62
r1 min.	0,6 mm
r2 min.	0,6 mm
Category	Single Row Ball Bearing
Enclosure	Open
Inventory	0.0
Size (mm)	15x35x11
Snap Ring	No
bore type:	Round
Width (mm)	11
Weight / LBS	0.099
maximum rpm:	360 RPM
Mass bearing	0.045 kg
Product Group	B00308
Cage Material	Steel
closure type:	Open
Inch - Metric	Metric
Temperature -	30 to +250 °
overall width:	11 mm

bore diameter:	15 mm
cage material:	Steel
Limiting speed	360 r/min
fillet radius:	0.6 mm
Bearing number	6202/VA201
Keyword String	Ball
Other Features	Deep Groove   Extreme Temperature Variant
finish/coating:	Uncoated
Rolling Element	Ball Bearing
Precision Class	ABEC 1   ISO P0
Long Description	15MM Bore; 35MM Outside Diameter; 11MM Outer Race Width; Open; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; Polyalkylene Glycol/Graphite Mixture Filled Internal Special Features; C0-M
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Outer Race Width	0.433 Inch   11 Millimeter
Outside Diameter	1.378 Inch   35 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Manufacturer Name	SKF
Weight / Kilogram	0.049
outer ring width:	11 mm
precision rating:	Not Rated
outside diameter:	35 mm
Internal Clearance	C0-Medium
d <sub>a</sub> min.	19.2 mm
D <sub>a</sub> max.	30.8 mm
r <sub>a</sub> max.	0.6 mm

Bore Diameter (mm)	15
snap ring included:	Without Snap Ring
internal clearance:	C0
Outer Diameter (mm)	35
Minimum Buy Quantity	N/A
r <sub>1,2</sub> min.	0.6 mm
resistance features:	Corrosion Resistant, Extreme Temperature
row type & fill slot:	Single Row Non-Fill Slot
static load capacity:	3.75 kN
d <sub>1</sub> ?	21.7 mm
D <sub>2</sub> ?	30.35 mm
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6202/VA201
Internal Special Features	Polyalkylene Glycol/Graphite Mixture Filled
Basic dynamic load rating C	8.06 kN
Limiting temperature T max.	250 °C
operating temperature range:	-20 to +480 °F
Basic static load rating (C0)	3,75 kN
Maximum Capacity / Filling Slot	No
Basic static load rating C <sub>0</sub>	3.75 kN