



Bearing No. 6202DDU

r	0.6
d	15 mm
D	35 mm
B	11 mm
C	11 mm
D_	35
C0	3.75
Z_	8
ra	0.6
fo	13.2
B_	11
DI_	19.547
SRI	3.01
SRE	3.16
DE_	31.453
DA_	5.953
D_a	31
KBRG	6161
SBRG	2
SRIN	0
bomp	0
SREX	0.03
yobi	6202DDU
SRIX	0.015
mass	0.045
SDM_	25.5
SREN	0
Bore	0.591 Inch 15 Millimeter
Noun	Bearing

LangID	1
UNSPSC	31171504
da min	19
r min.	0,6 mm
Weight	0,045 Kg
ALPHA_	0
C_conv	7650
da max	20,5 mm
GRS rpm	14000
Da max.	31 mm
ra max.	0,6 mm
da min.	19 mm
hidYobi	6202DDU
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Size (mm)	15x35x11
Enclosure	2 Seals
Snap Ring	No
Inventory	2130.0
Width (mm)	11
Prod_Type3	DGBB_SR_DD
Weight / LBS	0.09788
Inch - Metric	Metric
Product Group	B00308
Cage Material	Steel
Bearing number	6202DDU
Keyword String	Ball
Other Features	Deep Groove Rubber Seal
Enclosure Type	Contact Seal
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outer Race Width	0.433 Inch 11

	Millimeter
Outside Diameter	1.378 Inch 35 Millimeter
Long Description	15MM Bore; 35MM Outside Diameter; 11MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage;
Manufacturer URL	http://www.nskamericas.com
Inner Race Width	0 Inch 0 Millimeter
Manufacturer Name	NSK
Weight / Kilogram	0.045
Internal Clearance	C0-Medium
Bore Diameter (mm)	15
Outer Diameter (mm)	35
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6202DDU
Internal Special Features	No
(Grease) Lubrication Speed	14 000 r/min
Basic static load rating (C0)	3,75 kN
Basic dynamic load rating (C)	7,65 kN
Maximum Capacity / Filling Slot	No