



Bearing No. 6202N

a	2,06 mm
r	0.6
d	15 mm
D	35 mm
B	11 mm
C	11 mm
b	1,35 mm
fo	13.2
B_	11
ra	0.6
C0	3.75
D1	33,17 mm
D_	35
Z_	8
rn	0,5 mm
ro	0.4
DE_	31.453
SRI	3.01
D_a	31
DA_	5.953
SRE	3.16
DI_	19.547
yobi	6202N
mass	0.045
SBRG	2
bomp	0
KBRG	6101
SREX	0.03
SREN	0
SRIN	0

SDM_	25.5
SRIX	0.015
ALPHA_	0
r min.	0,6 mm
C_conv	7650
da max	20,5 mm
da min	19
Weight	0,045 Kg
LangID	1
ra max.	0,6 mm
Da max.	31 mm
Oil rpm	24000
da min.	19 mm
r0 max.	0,4 mm
hidYobi	6202N
GRS rpm	20000
hidTable	ecat_NSRDGB
Size (mm)	15x35x11
Prod_Type3	DGBB_SR_N_OT
Width (mm)	11
Bearing number	6202N
Bore Diameter (mm)	15
Outer Diameter (mm)	35
(Oil) Lubrication Speed	24 000 r/min
(Grease) Lubrication Speed	20 000 r/min
Basic dynamic load rating (C)	7,65 kN
Basic static load rating (C0)	3,75 kN