



Bearing No. K55X63X20

Fw	55 mm
Ew	63 mm
Bc	20 mm
Cr	40.3
Cu	11.7
P/S	S
C0r	73.5
Noun	Bearing
Bore	2.165 Inch 55 Millimeter
Width	0.787 Inch 20 Millimeter
UNSPSC	31171512
Weight	0.072 Kg
Retainer	Yes
Oil lub.	7800
Category	Needle Non Thrust Roller Bearing
Inventory	0.0
Separable	No
Component	Roller Assembly Only
Enclosure	Not Applicable
Closed End	Not Applicable
Grease lub.	5000
Bearing No.	K55X63X20
Shaft(max.)	55.000
Shaft(min.)	54.987
Weight / LBS	0.159
Housing(max.)	63.029
Housing(min.)	63.010
Inch - Metric	Metric

Product Group	B04144
Self Aligning	No
Other Features	Radial Roller Steel Cage
Bearing number	K55X63X20
Keyword String	Needle
Thrust Bearing	No
Rolling Element	Needle Roller Bearing
Outside Diameter	2.48 Inch 63 Millimeter
Long Description	55MM Bore; 63MM Outside Diameter; 20MM Width; Needle Roller Bearing; Roller Assembly Only; No Self Aligning; Retainer; Single Row of Rollers; No Separable
Manufacturer URL	http://www.koyousa.com
(Refer.)Mass(kg)	0.072
Manufacturer Name	KOYO
Weight / Kilogram	0.07
Bore Diameter (mm)	55
Outer Diameter (mm)	63
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.40.00.00
(Oil) Lubrication Speed	7800 r/min
Manufacturer Item Number	K55X63X20
Number of Rows of Rollers	Single Row
(Grease) Lubrication Speed	5000 r/min
Basic static load rating (C0)	73.5 kN
Basic dynamic load rating (C)	40.3 kN

