



Bearing No. 6202NR

f	1,12 mm
r	0.6
d	15 mm
D	35 mm
B	11 mm
C	11 mm
a	2,06 mm
b	1,35 mm
D1	33,17 mm
fo	13.2
C0	3.75
ra	0.6
D2	39,7 mm
Cy	2.9
ro	0.4
Dx	40.5
rn	0,5 mm
D_	35
B_	11
Z_	8
SRI	3.01
D_a	31
DE_	31.453
SRE	3.16
DA_	5.953
DI_	19.547
Noun	Bearing
SDM_	25.5
Bore	0.591 Inch 15 Millimeter

SRIX	0.015
SRIN	0
SREX	0.03
SREN	0
KBRG	6101
bomp	0
mass	0.045
yobi	6202NR
SBRG	2
da min	19
Weight	0,045 Kg
UNSPSC	31171504
r min.	0,6 mm
ALPHA_	0
da max	20,5 mm
LangID	1
C_conv	7650
hidYobi	6202NR
ra max.	0,6 mm
Da max.	31 mm
Oil rpm	24000
da min.	19 mm
GRS rpm	20000
r0 max.	0,4 mm
hidTable	ecat_NSRDGB
Category	Single Row Ball Bearing
Inventory	0.0
Size (mm)	15x35x11
Snap Ring	Yes
Enclosure	Open
Width (mm)	11
Prod_Type3	DGBB_SR_NR_OT

Weight / LBS	0.0992
Inch - Metric	Metric
Cage Material	Steel
Product Group	B00308
Bearing number	6202NR
Other Features	Deep Groove With Snap Ring
Keyword String	Ball
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outer Race Width	0.433 Inch 11 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Long Description	15MM Bore; 35MM Outside Diameter; 11MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; Yes Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Manufacturer URL	http://www.nskamericas.com
Outside Diameter	1.378 Inch 35 Millimeter
Weight / Kilogram	0.045
Manufacturer Name	NSK
Internal Clearance	C0-Medium
Bore Diameter (mm)	15
Outer Diameter (mm)	35
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	24 000 r/min
Internal Special	No

Features	
(Grease) Lubrication Speed	20 000 r/min
Basic static load rating (C0)	3,75 kN
Basic dynamic load rating (C)	7,65 kN
Maximum Capacity / Filling Slot	No