



### Bearing No. 6202ZZ

D	35 mm
d	15 mm
B	11 mm
C	11 mm
rn	0,5 mm
Bore	0.591 Inch   15 Millimeter
Noun	Bearing
da max	20 mm
UNSPSC	31171504
Weight	0,045 Kg
r min.	0,6 mm
ra max.	0,6 mm
da min.	19 mm
Da max.	31 mm
Category	Single Row Ball Bearing
Size (mm)	15x35x11
Snap Ring	No
Inventory	0.0
Enclosure	2 Metal Shields
Width (mm)	11
bore type:	Round
Weight / LBS	0.095
Inch - Metric	Metric
closure type:	Double Shielded
Product Group	B00308
Cage Material	Steel
bore diameter:	15 mm
Keyword String	Ball
overall width:	11 mm

cage material:	Steel
fillet radius:	0.6 mm
Other Features	Deep Groove
Bearing number	6202ZZ
Precision Class	ABEC 1   ISO P0
Rolling Element	Ball Bearing
finish/coating:	Uncoated
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Outside Diameter	1.378 Inch   35 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Outer Race Width	0.433 Inch   11 Millimeter
Long Description	15MM Bore; 35MM Outside Diameter; 11MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Stee
precision rating:	ISO Class 0
outside diameter:	35 mm
outer ring width:	11 mm
inner ring width:	11 mm
bearing material:	High Carbon Chrome Steel
Weight / Kilogram	0.05
Manufacturer Name	NTN
Bore Diameter (mm)	15
Internal Clearance	C0-Medium
Outer Diameter (mm)	35
internal clearance:	CN

snap ring included:	Without Snap Ring
Minimum Buy Quantity	N/A
static load capacity:	3600 N
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	19000 rpm
dynamic load capacity:	7750 N
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6202ZZ
Internal Special Features	No
manufacturer product page:	<a href="#">Click here</a>
(Grease) Lubrication Speed	19 000 r/min
operating temperature range:	-40 to 120 °C
Basic dynamic load rating (C)	7,75 kN
Basic static load rating (C0)	3,6 kN
Maximum Capacity / Filling Slot	No